AVTEO®

Plasma & LCD Carts







GMX-250

Solid Steel Carts

DIMENSIONS:

Load Capacity: 300 lbs

EXTERIOR

Height - 31"

Width - 41.5"

Depth - 27"

INTERIOR

Depth - 14.25"

Rack to Glass - 1.25"

Rack Units - 9RUs



Ask about customized design and prototype capabilities



The most **FEATURES** on the market:

- GMX-250S supports single display up to 42"
- ► **GMX-250M** supports single display up to 60"
- ► **GMX-250L** supports single display up to 65"; dual displays up to 60"
- ▶ 9RU of rack space
- Spring loaded adjustable v/c camera shelf
- One standard adjustable shelf
- 4" caters, 2 with brake
- Contemporary aluminum and glass construction
- Curved tempered locking glass door
- 6 port surge protector
- ▶ 100% Solid steel construction

Choose your OPTIONS:

- Additional rack mount shelf (US-1)
- Rack mounted AmpliVox© speaker module (PSM-200)
- Heavy duty 6" caster upgrade
- ▶ 6 port rack mount surge protector (RCK-PWR)
- Revolabs© shelfing system in various configurations for wireless microphone integration
- Custom cut rack shelf for LifeSize©, Polycom© & Cisco© codecs



Furniture Engineered For Today's Technology