



GMX-250L



GMX-250S

GMX-250

SOLID STEEL CARTS



DIMENSIONS:

Load Capacity: 300 lbs.

EXTERIOR

Height - 31"
Width - 41 1/2"
Depth - 27"

INTERIOR

Depth - 14 1/4"
Rack to Glass - 1 1/4"
Rack Units - 9RU

The most FEATURES on the market:

- ▶ GMX-250S supports single screen up to 42"
- ▶ GMX-250M supports single screen up to 55"
- ▶ GMX-250L supports single screen up to 65"; dual screens up to 55"
- ▶ 9RU of rack space
- ▶ Supports single or dual monitor
- ▶ Spring loaded adjustable v/c camera shelf
- ▶ One standard adjustable shelf
- ▶ 4" Casters, 2 with brake
- ▶ Contemporary aluminum and glass construction
- ▶ Curved tempered locking glass door
- ▶ 6-Port APC® surge protector

Choose your OPTIONS:

- ▶ Additional rack mount shelf (US-1)
- ▶ Rack mounted M-Audio® speaker module (PSM-200)
- ▶ Heavy duty 6" caster upgrade
- ▶ Single gang Wall Plates (3 RCA, VGA+Audio and VGA+Audio+LAN)
- ▶ PS-50 for TT-2 aps
- ▶ 6 Port rack mount APC® surge protector (RCK-PWR)
- ▶ Custom cut Rack Shelf for Lifesize®, Polycom® and Tandberg® codecs
- ▶ Revolabs® Shelving System in various configurations for wireless microphone integration



Available for immediate shipping



Ask about customized design and prototype capabilities

Furniture Engineered For Today's Technology

